

DIRTMASTER

KWIK-WAY

A HITCHDOC COMPANY

Standard Features:

- **Limitless Mobility:** Tow around the field, through the woods and then to a suburban backyard with an ATV/UTV, lawn tractor, truck or car at speeds up to 45 mph.*
- **Minimal disturbance:** Leave little to no marks with this compact and light-footed backhoe. Don't be concerned about ripping up lawn or effecting landscaping.
- **Solid Stance & Base:** Two pairs of stabilizers—one larger hydraulic pair positioned near the front and another manual pair toward the back of the machine—make for a solid working platform across any surface.
- **Easy Operation:** A beginner can easily learn and smoothly operate this backhoe with minimal experience by using the direction map that's installed next to the hydraulic levers.
- **Overbuilt to Outlast:** Decades have proven an established design and then manufactured from US prime steel and shipped from central Midwest USA.
- **Best-In-Class Motor:** Honda® engines are some of the most reliable small gas engines available—and arguably one of the best.
- **Long Lasting Finish:** A baked on Fire Engine Red powder-coat finish will resist damage and maintain through the toughest elements.
- **Bucket Variations:** Comes standard with a 12" bucket but can easily switch to a ripping tooth or other bucket widths in minutes.
- **Safe Transportation:** Use the lock pins on the stabilizers, boom and swing, along with the safety chains on the 2" ball coupler for a safe and smooth towing experience.

CONQUER ANY TERRAIN WITH THE ULTIMATE TOWABLE BACKHOE!



DIRTMASTER

KWIK-WAY

A HITCHDOC COMPANY

I-90 & US 71 | Jackson, MN
800.446.8222 | 507.847.4049 | Fax 507.847.5100
Sales@HitchDoc.com

WWW.HITCHDOC.COM

MADE IN
USA

DIRTMASTER

KWIK-WAY

A HITCHDOC COMPANY



Mechanical Specifications

Engine: Manual start with low oil indicator and shutdown.

Max HP: 8.4HP / 3600 rpm

Torque: 14.1 ft. lbs. / 2500 rpm

Fuel Capacity: 1.6 Gallons

Oil Capacity: 1.16 qt 10W30

Tire Size: 4.80/4.00 Pneumatic

Digging Depth: 78"

Horizontal Reach: 100"

Ripping Force: 2600 lbs.

Max Digging Radius: 140°

Lubrication: 25 Grease fittings at pivot points

Bucket Rotation: 147°

Tow Ball Size: 2" Ball

Towing Speed: 45 mph max* (10 mph with ATV/UTV)

Hydraulic Stabilizer Width: Down 100", Up (transport) 45"

Dry Weight: 1,175 lbs

Operation Weight: 1,260 lbs

Collapsed/Storage Dimensions: L 120" x W 64" x H 70"

Hydraulic Specifications

Hydraulic Tank: 12.5 gallon capacity

Hydraulic System: 13.93 gallon capacity
(including tank, cylinders, hoses, filter)

Hydraulic Fluid Filter: 10 micron filter

Gear Pump: Single stage

Hydraulic Fluid: Universal Hydraulic Fluid (all temps)

Options

53-0012: 9" Bucket

53-00321: 16" Bucket

53-01511: 14" Ripper Tooth

53-01611: Fenders with lights kit

DIRTMASTER



For more information, contact your local dealer or Sales@HitchDoc.com

WWW.HITCHDOC.COM

MADE IN
USA